

# PRODUCT DATA SHEET



## 1260 PAPER MASKING TAPE

**Painter's masking tape.**

### Product Features:

- \* Highly resistant to moisture and water.
- \* Creped paper is easily conformable.
- \* Excellent resistance to paint and thinners.
- \* Easy removal without adhesive residue, up to 7 days.
- \* Compatible with most common paints and lacquers.

### Applications:

- \* Ideal for automotive applications.
- \* Building and construction sites.
- \* Commercial and domestic masking applications.

### Product Specifications:

* Adhesive:	Natural rubber
* Backing:	Waterproof saturated crepe paper
* Total thickness:	0.130mm
* Colour:	Yellow
* Tensile strength:	87.5N / 25mm.
* Adhesion to steel:	4.8N / 25mm.
* Elongation:	8%.
* Temperature resistance:	80 deg. C (30 mins).
* Maximum width:	1510mm

**NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.**

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.