



Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|------------|-------------------------|------------|
| Document group: | 21-5048-0 | Version number: | 4.00 |
| Issue Date: | 18/11/2016 | Supersedes date: | 14/11/2016 |

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M(TM) Silane Glass Treatment AP115

Product Identification Numbers

70-0064-1268-1 70-0064-1269-9

1.2. Recommended use and restrictions on use

Recommended use

Adhesion promoter., Glass Adhesion Promoter

For Industrial or Professional use only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.

Serious Eye Damage/Irritation: Category 2.

Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product

label.

Signal word

DANGER!

Symbols

Flame | Exclamation mark |

Pictograms



Hazard statements

| | |
|------|-------------------------------------|
| H225 | Highly flammable liquid and vapour. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |

Precautionary statements

Prevention:

| | |
|-------|--|
| P210 | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. |
| P240 | Ground/bond container and receiving equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P233 | Keep container tightly closed. |
| P241 | Use explosion-proof electrical/ventilating/lighting equipment. |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280B | Wear protective gloves and eye/face protection. |
| P264 | Wash thoroughly after handling. |

Response:

| | |
|--------------------|--|
| P304 + P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P337 + P313 | If eye irritation persists: Get medical advice/attention. |
| P312 | Call a POISON CENTRE or doctor/physician if you feel unwell. |
| P370 + P378G | In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish. |

Storage:

| | |
|-------------|--|
| P403 + P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P403 + P235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |

Disposal:

| | |
|------|--|
| P501 | Dispose of contents/container in accordance with applicable local/regional/national/international regulations. |
|------|--|

2.3. Other assigned/identified product hazards

None known.

2.4. Other hazards which do not result in classification

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | CAS Nbr | % by Weight |
|--|----------------|--------------------|
| Propan-2-ol | 67-63-0 | 80 - 95 |
| Water | 7732-18-5 | 5 - 10 |
| 3-(Trimethoxysilyl)propyl glycidyl ether | 2530-83-8 | < 1 |

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide.
Carbon dioxide.

Condition

During combustion.
During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and

prevent explosive rupture.

Hazchem Code: •2YE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. **WARNING !** A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam designed for use on solvents, such as alcohols and acetone, that can dissolve in water. An Alcohol Resistant foam is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | CAS Nbr | Agency | Limit type | Additional comments |
|-------------|---------|----------------|--|-------------------------|
| Propan-2-ol | 67-63-0 | Australia OELs | TWA(8 hours):983 mg/m ³ (400 ppm);STEL(15 minutes):1230 mg/m ³ (500 ppm) | |
| Propan-2-ol | 67-63-0 | ACGIH | TWA:200 ppm;STEL:400 ppm | A4: Not class. as human |

3M(TM) Silane Glass Treatment AP115

| | | | | |
|--|--|--|--|--------|
| | | | | carcin |
|--|--|--|--|--------|

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl rubber.

Fluoroelastomer

Select and use gloves according to AS/NZ 2161.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid.

Appearance/Odour

Colourless Liquid with Alcohol Odour.

Odour threshold

No data available.

| | |
|---|---|
| pH | <i>Not applicable.</i> |
| Melting point/Freezing point | <i>Not applicable.</i> |
| Boiling point/Initial boiling point/Boiling range | 82.2 °C |
| Flash point | 11.7 °C [<i>Test Method</i> :Closed Cup] |
| Evaporation rate | 1.2 g/cm ² -hr |
| Flammability (solid, gas) | Not applicable. |
| Flammable Limits(LEL) | 2 % |
| Flammable Limits(UEL) | 12.5 % |
| Vapour pressure | 5,732.8 Pa [<i>@ 25 °C</i>] |
| Vapour density | 2.07 [<i>Ref Std</i> :AIR=1] |
| Density | 0.8 g/ml |
| Relative density | 0.8 [<i>@ 15.6 °C</i>] |
| Water solubility | 100 % |
| Solubility- non-water | <i>No data available.</i> |
| Partition coefficient: n-octanol/water | <i>No data available.</i> |
| Autoignition temperature | <i>No data available.</i> |
| Decomposition temperature | <i>No data available.</i> |
| Viscosity | <=3 mPa-s |
| Molecular weight | <i>No data available.</i> |
| Volatile organic compounds (VOC) | 732 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1] [<i>Details</i> :low solids less exempts] |

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Heat.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

None known.

Condition

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Dermal Defatting: Signs/symptoms may include localised redness, itching, drying and cracking of skin.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|--------------------------------|---------|--|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Inhalation-Dust/Mist(4 hr) | | No data available; calculated ATE >12.5 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| Propan-2-ol | Dermal | Rabbit | LD50 12,870 mg/kg |
| Propan-2-ol | Inhalation-Vapour (4 hours) | Rat | LC50 72.6 mg/l |
| Propan-2-ol | Ingestion | Rat | LD50 4,710 mg/kg |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Dermal | Rabbit | LD50 4,000 mg/kg |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 5.3 mg/l |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Ingestion | Rat | LD50 7,010 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|-------------------------|---------------------------|
| Propan-2-ol | Multiple animal species | No significant irritation |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Rabbit | Mild irritant |

Serious Eye Damage/Irritation

| Name | Species | Value |
|------|---------|-------|
|------|---------|-------|

3M(TM) Silane Glass Treatment AP115

| | | |
|--|--------|-----------------|
| | | |
| Propan-2-ol | Rabbit | Severe irritant |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Rabbit | Corrosive |

Skin Sensitisation

| Name | Species | Value |
|--|------------|--|
| Propan-2-ol | Guinea pig | Not sensitizing |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Guinea pig | Some positive data exist, but the data are not sufficient for classification |

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|--|----------|--|
| Propan-2-ol | In Vitro | Not mutagenic |
| Propan-2-ol | In vivo | Not mutagenic |
| 3-(Trimethoxysilyl)propyl glycidyl ether | In vivo | Not mutagenic |
| 3-(Trimethoxysilyl)propyl glycidyl ether | In Vitro | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|--|------------|---------|--|
| Propan-2-ol | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Dermal | Mouse | Not carcinogenic |

Reproductive Toxicity**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test result | Exposure Duration |
|--|------------|--|---------|-----------------------|----------------------|
| Propan-2-ol | Ingestion | Some positive developmental data exist, but the data are not sufficient for classification | Rat | NOAEL 400 mg/kg/day | during organogenesis |
| Propan-2-ol | Inhalation | Some positive developmental data exist, but the data are not sufficient for classification | Rat | LOAEL 9 mg/l | during gestation |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Ingestion | Not toxic to female reproduction | Rat | NOAEL 1,000 mg/kg/day | 1 generation |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Ingestion | Not toxic to male reproduction | Rat | NOAEL 1,000 mg/kg/day | 1 generation |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Ingestion | Some positive developmental data exist, but the data are not sufficient for classification | Rat | NOAEL 3,000 mg/kg/day | during organogenesis |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|-------------|------------|-----------------------------------|--|------------|---------------------|------------------------|
| Propan-2-ol | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Propan-2-ol | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Propan-2-ol | Inhalation | auditory system | Some positive data exist, but the data are not sufficient for classification | Guinea pig | NOAEL 13.4 mg/l | 24 hours |
| Propan-2-ol | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | poisoning and/or abuse |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|--|------------|---|--|---------|-----------------------|-------------------|
| Propan-2-ol | Inhalation | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 12.3 mg/l | 24 months |
| Propan-2-ol | Inhalation | nervous system | All data are negative | Rat | NOAEL 12 mg/l | 13 weeks |
| Propan-2-ol | Ingestion | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 400 mg/kg/day | 12 weeks |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Ingestion | heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system | All data are negative | Rat | NOAEL 1,000 mg/kg/day | 28 days |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

| Material | CAS Number | Organism | Type | Exposure | Test endpoint | Test result |
|--|------------|----------------|--------------|----------|---------------|-------------|
| Propan-2-ol | 67-63-0 | Algae | Experimental | 24 hours | EC50 | >1,000 mg/l |
| Propan-2-ol | 67-63-0 | Fathead minnow | Experimental | 96 hours | LC50 | 6,120 mg/l |
| Propan-2-ol | 67-63-0 | Crustacea | Experimental | 48 hours | EC50 | 1,400 mg/l |
| Propan-2-ol | 67-63-0 | Water flea | Experimental | 21 days | NOEC | 30 mg/l |
| 3-(Trimethoxysilyl)propyl glycidyl ether | 2530-83-8 | Common Carp | Experimental | 96 hours | LC50 | 55 mg/l |
| 3-(Trimethoxysilyl)propyl glycidyl ether | 2530-83-8 | Water flea | Experimental | 48 hours | EC50 | 473 mg/l |
| 3-(Trimethoxysilyl)propyl glycidyl ether | 2530-83-8 | Green algae | Experimental | 96 hours | EC50 | 350 mg/l |
| 3-(Trimethoxysilyl)propyl glycidyl ether | 2530-83-8 | Water flea | Experimental | 21 days | NOEC | >=100 mg/l |
| 3-(Trimethoxysilyl)propyl glycidyl ether | 2530-83-8 | Green algae | Experimental | 96 hours | NOEC | 130 mg/l |

12.2. Persistence and degradability

| Material | CAS Number | Test type | Duration | Study Type | Test result | Protocol |
|--|------------|-----------------------------|----------|--------------------------------|-------------------------------|------------------|
| 3-(Trimethoxysilyl)propyl glycidyl ether | 2530-83-8 | Experimental Hydrolysis | | Hydrolytic half-life | 6.5 hours (t _{1/2}) | Other methods |
| 3-(Trimethoxysilyl)propyl glycidyl ether | 2530-83-8 | Experimental Biodegradation | 28 days | Dissolv. Organic Carbon Deplet | 37 % weight | Other methods |
| Propan-2-ol | 67-63-0 | Experimental | 14 days | BOD | 86 % weight | OECD 301C - MITI |

3M(TM) Silane Glass Treatment AP115

| | | | | | | |
|--|--|----------------|--|--|--|----------|
| | | Biodegradation | | | | test (I) |
|--|--|----------------|--|--|--|----------|

12.3 : Bioaccumulative potential

| Material | CAS Number | Test type | Duration | Study Type | Test result | Protocol |
|--|------------|---|----------|------------|-------------|---------------|
| 3-(Trimethoxysilyl)propyl glycidyl ether | 2530-83-8 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| Propan-2-ol | 67-63-0 | Experimental Bioconcentration | | Log Kow | 0.05 | Other methods |

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Dispose of waste product in a permitted industrial waste facility.

SECTION 14: Transport Information**Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

UN No.: UN1219

Proper shipping name: ISOPROPANOL SOLUTION

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: II

Special Instructions: Limited quantity may apply

Hazchem Code: •2YE

IERG: 16

International Air Transport Association (IATA) - Air Transport

UN No.: UN1219

Proper shipping name: ISOPROPANOL SOLUTION

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: II

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN1219

Proper shipping name: ISOPROPANOL SOLUTION

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: II

Marine Pollutant: Not applicable.

Special Instructions: Limited quantity may apply

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

Poison Schedule: This product has not been assessed for poisons scheduling as the product is intended for industrial and professional use only.

SECTION 16: Other information

Revision information:

Conversion to GHS format SDS.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au