

**STYLUS 2907 POLYETHYLENE  
ISOLATION/PIPE WRAP TAPE**

**DESCRIPTION:**

A flexible, conformable polyethylene film coated with an aggressive rubber adhesive. Colour - Black.

**PERFORMANCE  
FEATURES:**

Product has a smooth consistent unwind for easy application even at sub zero temperatures. Tape is resistant to moisture acids, alkalis and to salt solutions. Has electrical insulation properties.

**TECHNICAL  
SPECIFICATIONS:**

<b>Adhesion:</b>	-	<b>320gm/cm</b>
<b>Thickness:</b>	-	<b>0.25mm</b>
<b>Tensile Strength:</b>	-	<b>3.2Kg/cm</b>
<b>Elongation:</b>	-	<b>350%</b>
<b>Temperature Resistance:</b>	-	<b>60°C</b>
<b>Dielectric Strength:</b>	-	<b>65Kv/mm</b>
<b>Water Vapour Permeability (at 38 °C &amp; 90% RH)</b>	-	<b>5gm/m<sup>2</sup> per 24hr</b>

**SIZES AVAILABLE:**

12mm to 720mm x 33M

**APPLICATIONS:**

Used to protect pipelines against corrosion and mechanical damage, joining polyethylene sheeting, and sealing joins of polyethylene tubing protecting pipes. Also used for sealing agricultural polythene sacks. Ideal as an electrolysis barrier between dissimilar metals eg: between cladding and steel purlins in the construction industry.

The above information is given in good faith for guidance only and not specification purposes. All data is based upon average values, the Purchaser shall be responsible for determining the suitability of this product for their purposes.

September 2007