

## tesa® 61105

### EPDM rubber closed cell single sided foam tape 9.5mm thick (black)

tesa 61105 is a 9.5mm thick closed cell EPDM foam tape with an acrylic adhesive on one side. The EPDM foam is non-staining, non-corrosive and electrically non-conductive. The foam offers high temperature resistance (-40°C to 105°C) as well as excellent resistance to UV, ozone and weathering, making it ideal for outdoor use.

tesa 6110 Series is FDA approved to Section 177.26 (non-poisonous, non carcinogenic) and will not contaminate drinking water. It complies with auto industry standards and is plastic compatible. The EPDM foam is also non-toxic and flame retardant to FMVSS 302\*

\*Federal Motor Vehicle Safety Standard.

## Main Application

tesa 6110 Series foam tape is an ideal sealing solution for a wide range of sealing applications across automotive, marine, food and beverage, enclosures and window glazing type markets.

### Application ideas:

- Sealing electrical enclosures and switch cabinets
- Sealing exterior and interior lighting
- Sealing industrial access doors and hatches
- Sealing hatches on boats
- Sealing domestic and commercial glazing systems
- Sealing externally mounted air conditioning equipment

## Technical Data

▪ Backing material	EPDM rubber foam	▪ Temperature resistance from	-40 °C
▪ Total thickness	9500 µm	▪ Temperature resistance up to	105 °C
▪ Type of adhesive	acrylic	▪ Compression Set	7 %
▪ Adhesion to steel	12 N/cm	▪ Hardness - Shore 00	37
▪ Elongation at break	175 %	▪ Water Tightness	100 %
▪ Tensile strength cm2	54 N/cm²		

## Properties

▪ Suitable for die cutting	yes	▪ Water resistance	● ● ● ●
▪ UV-resistance	● ● ● ●	▪ Flame retardant	● ● ● ●

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=61105>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.