



Diamond Guard 400 is a premium protection film specifically designed for the protection of laminate benchtops and other smooth surfaces. It is extensively used for the protection of kitchen bench tops during construction, transport and install.

Benefits


- Will not creep and wrinkle after application.
- Prevents scratching and provides a barrier against paint, stains etc.
- Easily removed
- Can be left for up to 3 months

Application Instructions

- This product is designed for the protection of smooth surfaces.
- Obviously, adhesion will be reduced on dusty surfaces. Cleaning prior to use is recommended
- Diamond Guard 400 must be removed after a maximum of 12 weeks
- A test is always recommended prior to full production application
- It is the users responsibility to determine suitability for use. If in doubt contact technical services for advice.

Uses

- Protection of kitchen bench tops and many other smooth surfaces.



SPECIFICATIONS	Diamond Guard 400
Construction	Consists of low density polyethylene film with an acrylic based pressure sensitive adhesive on one side.
Colour	Black/White
Film Thickness	0.12mm
Adhesion	600g/25mm
Roll Size	640mm x 100m
Application Conditions	The surface must be free from oil, dust, solvents and separating agents. Room temperature (10° - 40°)
Resistance	Against Moisture: Good, Against Oil: Moderate, Against Solvents: Moderate UV - 6 Months
Storage Conditions	Room temperature. Storage time max. 12 months from date of manufacture.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technical changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Any warranty applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

