productinformation

tesa[®] 6012 Manual multi-track desk dispenser

The tesa[®] 6012 is a multi-track desk dispenser for tesa[®] packaging tape of up to 66 m in length and a width of 50 mm. Due to the extra-wide blade design, the dispenser can easily be loaded with one roll of tape 50mm wide or with two rolls of tape 25mm wide at the same time (e.g. different widths or colours). The tesa[®] 6012 multi-tape dispenser is a sturdy metal-base all-purpose dispenser for production and warehouse use, for sealing small packages and for taping wrapping paper. In addition, the integrated safety-blade cover helps to prevent injuries when the dispenser is not in use. tesa[®] 6012 can be fastened securely on packing tables with the supplied clamp or screws (four screw holes are prepared). Tape is easily dispensed and cut along the extra wide serrated blade.

Main Application

- The tesa® 6012 is a manual tape dispenser for packaging tape up to 66 m in length and a width of 50 mm
- The manual dispenser is mostly used in production and warehouses, for sealing small packages and for taping wrapping paper
- Two tape rolls with a max. width of 25mm can be inserted simultaneously
- A safety blade cover helps to prevent injury

Technical Data

Core diameter	3 inch	•	Mode of drive
Type of tape	single-sided	•	Weight
Application purpose	packaging	•	Max. roll diameter
Length	175 mm	•	Type of applicator
Width	67 mm	•	Max. roll width
Height	130 mm		

²age 1 of 1 - as of 31/10/2019 - ena

For latest information on this product please visit <u>http://l.tesa.com/?ip=06012</u>

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



manual 610 g 145 mm table 50 mm