

# 3M™ Extreme Sealing Tape 4412N



From rain gutters to flashing and vents  
a sure winner over traditional sealants

## 3M™ Extreme Sealing Tape 4412N – rolls on fast and looks good

- Sticks on contact to many metals and plastics without drying time, dripping, oozing, and clean-up
- No sticky mess on hands
- Conforms over contours, edges, rivets and screw heads for a water tight seal
- No caulking guns to buy, clean and store, and no empty cartridges for disposal
- Paintable to color blend with the adjoining surfaces
- Neat and precise looking for aesthetics

## Over time even more extreme advantages become obvious

- Holds securely through sun, rain, snow, temperature extremes, and abrasion
- Stays flexible to compensate for vibration and thermal expansion/contraction
- No cracking and crumbling

## Seaming and sealing ideas

- Parapet walls
- Trailer home roofs
- Metal buildings
- Vent stacks and vent windows
- Gutters and downspouts
- Skylights
- Patching
- Trailer and RV roofs
- Metal enclosures



# 3M™ Extreme Sealing Tape 4412N – rolls on fast and tight and stays that way



5 Simply clean with a solution of water and isopropyl alcohol and wipe dry.



6 Sticks on contact exactly where you roll it on. No drips and oozing. No waiting.



7 Roll down with a soft roller to conform over contours, seam edges, rivets, or screw heads.



8 Peel off the protective release liner.



9 Burnish once more to optimize adherence and conformance to uneven surfaces.



From rooftops to underground cable enclosures – durable sealing through heat, cold, and weather without cracking or edge lifting.



## Product Information

Product/Color	Backing/Adhesive	Tape Thickness (mm)	Tensile Strength (N/cm)	90° Peel Strength (N/cm)				Widths (mm)	Comments
				Aluminum	Steel	PVC	ABS		
4412N Translucent White	Ionomer film/ Pressure sensitive acrylic	2.0	21	9 (18*)	7 (17*)	9 (20**)	2 (20**)	25, 50, 60, 75	Resists yellowing, cracking, and edge lifting

\* With 3M™ Adhesion Promoter 111 \*\* With 3M™ Primer 94

**Note:** This technical information and data should be considered representative or typical only and should not be used for specification purposes.

**Warranty and Limited Remedy:** 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If the 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

**Limitation of Liability:** Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.



### Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06  
St. Paul, MN 55144-1000  
800-362-3550 . 877-369-2923 (Fax)  
www.3M.com/vhb

3M is a trademark of 3M Company.

Printed in U.S.A  
© 3M 2009  
70-0709-4048-4