

# PRODUCT DATA SHEET



## 400 SERIES FOAM SEALING TAPE Single Sided Open Cell Polyurethane.

### Product Features:

- \* Cushions and absorbs shock.
- \* Acrylic adhesive for permanent mounting.
- \* Good noise suppression properties.
- \* Good thermal stability.

### Applications:

- \* Sealing air conditioning joints.
- \* Weatherseal strip around door and window frames.
- \* Used in concrete formwork.
- \* Air and or oil filtration.

### Product Specifications:

|                           |                      |
|---------------------------|----------------------|
| * Thickness:              | 6mm                  |
| * Density:                | 31kg per cubic metre |
| * Colour:                 | Grey                 |
| * Tensile strength:       | 130kPa               |
| * Tear resistance:        | 400N per metre       |
| * Temperature resistance: | 90 deg. C            |
| * Compression set:        | 10% @ 75% deflection |
| * Elongation:             | 200%                 |
| * Maximum width:          | 1200mm               |

**NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.**

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.