

PRODUCT DATA SHEET



100 SERIES FOAM SEALING TAPE

Single sided Nitrile foam Rubber.

Product Features:

- * Cushions and absorbs shock.
- * Resists UV, aging, fungi and most chemicals.
- * Excellent resistance to wear and abrasion.
- * High temperature resistance.
- * Laminated with a long life acrylic adhesive.
- * Dimensionally stable - will not ooze.

Applications:

- * Ideal for die cutting and gasketing.
- * Automotive and marine door and hatch seals.
- * Spray booth door seals.

Product Specifications:

* Thickness:	3, 6, 9 and 12mm
* Density:	112 to 192 kg per cu. m
* Colour:	Black
* Maximum width:	1200mm
* Hardness:	35 to 55 (Shore 00)
* Tensile strength:	483 kPa
* Elongation:	100%
* Compression deflection:	35 to 62 kPa
* Compression set:	25% max
* Water absorption:	5% by volume
* Temperature resistance:	-29 to 104 deg. C
* Flammability rating:	100mm per minute max.
* Chemical resistance:	Good

NOTE: When applying pressure sensitive adhesives, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.