

# PRODUCT DATA SHEET



8832 DOUBLE SIDED TAPE.

Double sided adhesive coated foam.

## Product Features:

- \* High strength long life acrylic adhesive.
- \* Flexible and conformable to match irregular surfaces.
- \* Superior bonding to the latest auto finishes.
- \* Excellent UV, solvent and weather resistance.
- \* Mounting exterior trim and side moldings on vehicles.
- \* Urethane foam provides shock absorption.
- \* Permanent fixing of signs and nameplates.
- \* Good low temperature flexibility.
- \* Excellent hydrolytic stability.
- \* Sound damping.
- \* Gasketing.
- \* Manufactured to ISO 9002.

## Product Specifications:

- |                           |   |
|---------------------------|---|
| * Carrier:                | Closed cell polyurethane foam   |
| * Max width:              | 1450mm  |
| * Adhesive:               | Acrylic   |
| * Thickness:              | 0.8mm   |
| * Colour:                 | Black   |
| * Liner:                  | Green HDPE  |
| * Density:                | 33 pound per cu ft  |
| * Hardness:               | 32 (Shore A)  |
| * Tensile strength:       | 280 pound per sq in   |
| * Elongation:             | 350%  |
| * Adhesion to steel:      | 105 ounces per in   |
| * Temperature Resistance: | 90 deg C.   |
| * Hydrolytic stability:   | Min 80% retention of tensile properties<br>2 weeks at 85 deg. C and 100% R.H. |

## Approvals from:

- \* General Motors Corporation - USA
- \* Chrysler Jeep - USA
- \* Ford Motor Co. - USA
- \* Nissan Motor - Aust.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.