

PRODUCT DATA SHEET



130 ALL WEATHER TAPE

UV Stabilised Polyethylene Tape.

Product Features:

- * Aggressive adhesive to polyethylene, PVC and other surfaces.
- * Resists water, oil, acid and alkalies.
- * Long aging acrylic adhesive.
- * Hand tearable - no dispenser required.

Applications:

- * Suitable for joining polyethylene sheeting.
- * General purpose exterior joining and repairs.
- * Repair or reinforce greenhouses and tunnel houses.
- * Used as overwrap on piping and electrical binding.
- * Anti shatter and surface protection.
- * Waterproofing and sealing.

Product Specifications:

* Adhesive:	Solvent based Acrylic
* Backing:	Polyethylene
* Backing thickness:	0.100mm
* Total thickness:	0.135mm
* Maximum width:	1200mm
* Colour:	Clear
* Tensile strength:	55N per 25mm
* Adhesion to steel:	10N per 25mm
* Temperature resistance:	80 deg. C
* Elongation:	450%
* UV resistance:	Excellent

NOTE: When applying pressure sensitive adhesives, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.