

# DIAMOND GUARD 346B - HIGH TACK



Diamond Guard - 346B is a premium protection film with a medium/high level of adhesion. It is a UV stable film and is often used for protection of windows and frames on construction sites. Diamond Guard - 346B will also offer an effective means of protection for laminates, melamine board and other smooth surfaces.

## Benefits

- Easily applied by hand - no specialist equipment required.
- Self adhesive, does not require tape or additional fixing.
- Stays in place - once smoothed into position Diamond Guard - 346B will not fall away.
- Forms an effective barrier against splashes and prevents scratching.
- Removes cleanly.
- UV protected - maximum 6 months.
- Versatile - can be used on various smooth and slightly textured surfaces.

## Application Instructions

- Obviously, adhesion will be reduced on dusty surfaces. Cleaning prior to use is recommended.
- Avoid stretching film during application.
- Diamond Guard - 346B must be removed after a maximum of 6 months.
- Always check that Diamond Guard - 346B is stuck firmly to substrate before commencing work.
- A test area is always recommended prior to full application.
- It is the users responsibility to determine suitability for use. If in doubt contact technical services for advice.



## Uses

- Protecting the window frame and glass from cement render etc.
- Protecting most smooth, low gloss surfaces etc.



SPECIFICATIONS	Diamond Guard 346B - High Tack
Construction	Consists of a low density polyethylene film with an acrylic based pressure sensitive adhesive on one side.
Colour	Blue
Film Thickness	0.07mm
Adhesion	250g/25mm
Roll Size	1220mm x 100m
Application Conditions	The surface must be free from oil, dust, solvents and separating agents. Room temperature (10° - 40°)
Resistance	Against Moisture: Good. Against Oil: Moderate. Against Solvents: Moderate. UV - Resistance: Recommended Max. 6 Months.
Storage Conditions	Room temperature. Storage time max. 6 months from date of manufacture

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technical changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Any warranty applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.