

PRODUCT DATA SHEET



620 FOIL TAPE

Single Sided Reinforced Aluminium Foil

Product Features:

- * Fibre reinforced aluminium foil.
- * Used for joining and sealing insulation, cold air ducting, chilled water piping, air conditioning and refrigeration, lagging and roofing insulation.
- * Good resistance to solvents, chemicals, UV, aging and heat.

Product Specifications:

| | |
|---------------------------|---|
| * Adhesive: | Acrylic |
| * Backing: | Aluminium foil with LDPE laminate, and glass fibre reinforced |
| * Total thickness: | 0.135mm |
| * Release paper: | White siliconised paper |
| * Colour: | Silver |
| * Tensile strength: | 175N per 25mm |
| * Adhesion to steel: | 9N per 25mm |
| * Temperature resistance: | 90 deg C. |
| * Elongation: | 5% |

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.