

PRODUCT DATA SHEET



22 ELECTRICAL TAPE

Single Sided Polyimide Film

Product Features:

- * Strong, durable, stable backing.
- * Puncture and tear resistant.
- * High temperature resistance.
- * Excellent chemical resistance.
- * Used in DC mining and traction motors.
- * Masking off on printed circuit boards.
- * Gold finger protection during wave soldering.
- * No adhesive residue.

Product Specifications:

* Adhesive:	Silicone
* Backing:	Polyimide film
* Backing thickness:	0.025mm
* Total thickness:	0.063mm
* Colour:	Amber
* Adhesion to steel:	7N per 25mm
* Temperature resistance:	260 deg C.
* Volume resistivity (200C):	2.8×10^{12} ohms.cm
* Dielectric strength:	6500 volts
* Dielectric constant (1 kilocycle/sec):	3.2
* Dissipation factor (1 kilocycle/sec):	0.0017
* Maximum width:	1000mm

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.

MP250908