# PRODUCT DATA SHEET



## TFF1

Fluropolymer coated cloth tape.

#### **Product Features:**

- \* Excellent release qualities.
- \* Abrasion resistant, low friction surface.
- Chemical resistant.
- Excellent temperature resistance.
- Excellent strength and durability.

#### **Applications:**

- \* Covering the heat sealing surface of L-bar sealers, impulse sealers and bag sealers.
- \* Guide rails and chute linings.
- Packaging equipment.
- \* Non stick roller covering.
- Reusable release surface.

### **Product Specifications:**

\* Backing: PTFE coated cloth

\* Adhesive: Silicone
\* Total thickness: 0.135mm
\* Liner: N/A
\* Colour: Brown

\* Tensile strength: 30kg per25mm
\* Adhesion to steel: 0.9kg per 25mm

\* Temperature resistance: 260 deg C. short term

\* Elongation: 4%\* Maximum width: 480mm

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.