

# PRODUCT DATA SHEET



## UHMW TAPE

Ultra High Molecular Weight Polyethylene Film.

### Product Features:

- \* Clear abrasion resistant Polyethylene film.
- \* High tack acrylic pressure sensitive adhesive on one side.
- \* Good quick stick makes application easy.
- \* Polyethylene film provides a 'slippery surface'.
- \* Provides low coefficient of friction to reduce wear.

### Applications:

- \* Guide rails and chute linings.
- \* Sliding doors and drawers.
- \* Sewing and assembly tables.
- \* Allows products to slide easier.

### Product Specifications:

* Backing:	UHMW Polyethylene
* Adhesive:	Acrylic
* Total thickness:	0.178mm
* Liner:	White paper
* Colour:	Translucent
* Maximum width:	635mm
* Adhesion to steel:	22N per 25mm
* Temperature resistance:	66 deg. C

**NOTE: When applying pressure sensitive adhesives, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.**

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.

MP110105